

E5000 400V 50Hz

ENERGY AT FAIR PRICE



Simple professional generator. Pramac has designed this generator to ensure a high performance level at attractive price. Powerful and strong generator; easy to maintain, it will be soon essential to all your activities.

Standard Equipment

Starting system Recoil

Main Features		
Frequency	Hz	50
Voltage	V	400
Power factor	cos φ	0.8
Single Phase Power factor	cos φ	0.9
Phase and connection		3

Power Rating		
Standby power LTP	kVA	6.3
Standby power LTP	kW	5.0
Continuous power COP	kVA	5.4
Continuous power COP	kW	4.3

Single Phase Power Rating		
Single phase standby power LTP	kVA	3.8
Single phase continuous power COP	kVA	3.5

Ratings definition (According to standard ISO8528 1:2005)



E5000 400V 50Hz

Engine Specifications

Brand		Honda
Model		GX270 Recoil
Engine cooling system		Air
Displacement	cm³	270
Aspiration		Natural
Speed governor		Mechanical
Operating Speed-Nominal	rpm	3000
Oil capacity	L	1.1
Fuel		Gasoline
Starting system		Recoil
Fuel consumption @ 75% PRP	L/h	1.66



Alternator Specifications

Class		Н
IP protection		23
Poles		2
Voltage tolerance	%	6

Dimensional data

Length	(L) mm	715
Width	(W) mm	540
Height	(H) mm	490
Dry weight	kg	61
Fuel tank capacity	L	5.3

Autonomy

Running time @ 75% PRP h 3.19

Noise level

Guaranteed noise level (LWA)	db(A)	97
Noise pressure level @ 7 mt	db(A)	69



E5000 400V 50Hz

GENSET CONTROL

COMMANDS:

Selector switch: OFF - ONStarting systems: Recoil

- Fuel Cock

PROTECTIONS STANDARD:

- Thermal protection

- Oil Guard

SOCKET TYPE

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 16A IP44	1
3P+N+T CEE 400V 16A IP44	1





E5000 400V 50Hz

ACCESSORIES

TRANSPORTATION KIT

with fix handles



TRANSPORTATION KIT

with folding handles



